







Butterfly valve A480/A490

- Reduced torque
- 3-A gaskets
- More resistant and reliable
- EHEDG approval

Ball valve A640

- Constant torque
- Controlled ball movement
- Piggable DIN & OD

Actuator A940

- More resistant and reliable
- One model with/without C-TOP S control unit
- One single support for all sizes

C-TOP S control unit

- Hall Effect sensors on PCB
- Auto set-up
- Communication: digital & As-I

BALL VALVE A640



BUTTERFLY

VALVE **A480** A490



ACTUATOR A940



CONTROL UNIT **C-TOPS**



SEAT


- Controlled O-rings compressibility
- Limited ball movement under pressure (avoiding metal-to-metal contact)

FULLY PIGGABLE

Specific balls for OD & DIN


(full-bore piggable valves)

 Constant torque throughout the life of the valve




BRACKETS

• New bracket design: the same model and size for all valve sizes (DN25/1" - DN100/4")



- Specific drills for the assembly of the new actuator brackets



BODY

New design of valve body

- Reduced operating torque
- Increased endurance
- Higher reliability
- Improved bushing retention
- EHEDG approval





3 FOR CE SUBPLE CONTROL

New T-shaped design for better retention and lower torque


BRACKETS


- Specific drills for the assembly of the new actuator brackets
- New bracket design: the same model and size for all valve sizes (DN25/1"-DN100/4")



- Improved shaft and spring endurance make it highly reliable
- Standard design prepared for accessories
- One actuator model: with/without C-TOP S control head








- Easy assembly with a bracket and only 2 screws

- Base mounted solenoid valves (up to 3)
- Opaque cover with translucent upper part
- Sensors on PCB
- Communication: Digital, AS-I
- Push-button setup (auto-setup)
- Memory for 3 positions (+ 1 external sensor)







INOXPA S.A.U.

Telers, 60 17820 Banyoles - Spain Phone +34 972 57 52 00 Fax +34 972 57 55 02 inoxpa@inoxpa.com

www.inoxpa.com